

LMI Filter Information

		Instruments		
		Instrumentation Main Page		
		<u>Facility Instruments:</u>		
Quick Links	LDT Observer Information Home		Large Monolithic Imager (LMI)	
	Instrumentation	Facility	DeVeny Optical Spectrograph	At the Telescope
	Applying for Observing Time	LDT Science Schedule	NIR Spectrograph (NIHTS)	Observing Planning
	Observing Run Planning	LDT Staff	<u>Visitor / PI Instruments:</u>	Applying for Observing Time
	At the Telescope (Printable Logsheets)	Telescope		Planning Checklist
	Target of Opportunity (ToO) Policies	Site Information		Remote Observing
	Weather	High-Res Spectrograph (EXPRES)		Target of Opportunity (ToO) Policies
	Acknowledging LDT	Speckle Imager (QWSSI)		Remote Observing
	After Your Observing Run	Selected Technical Publications		LDT Startup Procedures
	First-Time Users	High Speed Imager (POETS)		Closure Conditions
	Logistics	NIR Spectrograph (RIMAS)	Target Lists	First-Time Users
	LDT Important Notes			Logistics
		<u>User Manuals:</u>		
		LMI Manual		
		DeVeny Manual		
		NIHTS Manual		

The information on this page is for quick reference. Please consult the [LMI Users Manual](#) for more detailed information, including filter transmission curves and data.

LMI Filters:

Currently available filters for LMI are given in the table below.

- The value shown under **FITS Header** will appear in the FILTERS keyword of your image headers.
- The **Pattern String** is the LOUI display string you need to use if creating a [Telescope Motion Pattern File](#).
- **Focus Offset** indicates how much additional focus offset is applied to the Active Optics System to account for filter refraction – it is most helpful for determining which filters are parfocal.
- For taking dome flats (using the CLSD lamps at 12V), an approximate **Exptime for 20k counts** is provided. For the bluest filters (both broad- and narrow-band), the usual "LMI Lamps" do not provide sufficient flux in the bandpass to easily collect dome flats. For these, a second exposure time is listed using the Photo Floods (a.k.a. IGRINS lamps) on the lamp boom. These are 600-W photographic flood lamps with very short lifetimes – please use sparingly.
- For selected filters, the **Central Wavelength** and **Filter Width** (both in Å) are listed.

Sample dome flats for the various filters taken over time can be found on the [LMI Filter Characterization](#) page.

Filter	FITS Header Value	Pattern String	Focus Offset (μm)	Exptime for 20k counts (seconds)	Filter Central Wavelength (Å)	Filter Width (Å)
<u>Non-Filter Positions</u>						
OPEN	OPEN	OPEN	0			
DARK	DARK	DARK	N/A			
4 Hole Mask	4HOLEMASK	4Hole				
<u>Johnson-Cousins Filters</u>						
U	U	U	+140	178 / 4*		
B	B	B	+105	9		
V	V	V	+105	5		
R	R	R	+140	3.5		
I	I	I	+140	3.3		
<u>Sloan (SDSS) Filters</u>						
SDSS u'	SDSS-U	SL-u	+180	313 / 4.5*		
SDSS g'	SDSS-G	SL-g	+180	4.5		
SDSS r'	SDSS-R	SL-r	+180	3.5		
SDSS i'	SDSS-I	SL-i	+180	4.25		
SDSS z'	SDSS-Z	SL-z	+180	3.25		
<u>Other Broad Band Filters</u>						
V+R	VR	VR	+185	2.5	6091.7	1763.9
Yish	YISH	YISH	+105	26		
<u>General Narrow Band Filters</u>						
[OIII]	OIII	OIII	+205	180	5001.7	25.5
H-On	HALPHAON	Ha-on	+155	115	6564.9	30.1
H-Off	HALPHAOFF	Ha-off	+155	37	6459.1	114.6
<u>Wolf-Rayet Filters</u>						
WC	WR-WC	WC	+165	115	4660.4	49.5
WN	WR-WN	WN	+160		4690.9	49.6
CT	WR-CT	CT	+170		4756.1	54.6
<u>Comet Filters</u> (Note: These filters are 4 inches round and suffer some vignetting on LMI)						
Ultraviolet Continuum	UC	UC	+175	500** / 80*	3449	79
Blue Continuum	BC	BC	+175	130 / 3.5*	4453	61
Green Continuum	GC	GC	+175	119	5259	56
Red Continuum	RC	RC	+175	70	7133	58
C ₂	C2	C2	+175	46	5135	119
C ₃	C3	C3	+175	250	4063	58
CN	CN	CN	+175	480 / 14*	3869	56
CO+	CO+	CO+	+175	160	4266	64
H ₂ O+	H2O+	H2O+	+175		7028	164
OH	OH	OH	+175	480** / 400*	3097	58
NH	NH	NH	+175		3361	54
<u>Assorted Other Filters</u> (inquire if you want to use, as they may not be readily available)						
W032	W032	W032	+176		5300	
5027	5027	5027	+130		5027	
K1593	K1593	K1593	+194		5010	

** OH & UC counts were at about the bias level for this exposure time using the CLSD lamps at 12V.

* Using the photo floods (a.k.a. IGRINS lamps) on the LMI lamp boom